



BALCONY LOAD DO NOT EXCEED 1,200 LBS. BALCONY RAILING DESIGNED AND BUILT BY OTHERS. WHEN DRILLING IF HIT REBAR, DON'T CONTINUE DRILLING. STAY CLEAR OF THE REBAR.

- NOTES:
1. CRITICAL DIMENSIONS ARE GIVEN. OTHERS MAY BE SCALE MEASURED. SEE SHEET S-1 FOR BEARING WALL LOCATION DIMENSIONS.
  2. INTERIOR WALLS ARE DIMENSIONED TO THEIR CENTERLINE UNLESS OTHERWISE NOTED.
  3. INTERIOR WALL THICKNESS SHOWN IS 4 1/2", 3 1/2" FRAMING PLUS 1/2" WALL BOARD ON BOTH SIDES.
  4. RAD-C INDICATES THE RADIUS TO THE CENTER OF THE FLOOR.
  5. ALL BEDROOMS THAT DO NOT HAVE AN ALTERNATE EXIT MUST HAVE WINDOW QUALIFIED FOR EGRESS. MINIMUM WIDTH OF OPENING 20". MINIMUM HEIGHT 24". MIN. CLEAR OPEN AREA 5.7 SQ. FT. MAXIMUM HEIGHT FROM THE FLOOR TO THE BOTTOM OF THE OPENING 44".
  6. WINDOWS FOR BEDROOMS MUST MEET EGRESS AS STATED. OTHER WINDOWS CAN BE SMALLER. EXTERIOR DOORS: THERE MUST BE ONE 36" EGRESS DOOR. U FACTOR MUST BE EQUAL OR BETTER THAN ENERGY REPORT. PERFORMANCE LABELS MUST STAY ON WINDOWS AND EXTERIOR DOORS UNTIL FINAL INSPECTION.
  7. ENCLOSED ACCESSIBLE SPACE UNDER STAIRS SHALL HAVE WALLS, UNDER-STAIR SURFACE AND ANY SOFFITS PROTECTED ON THE ENCLOSED SIDE WITH 5/8" TYPE "X" GYPSUM BOARD.
  8. LANDINGS OR FLOORS AT THE REQUIRED EGRESS DOOR SHALL NOT BE MORE THAN 1 1/2" LOWER THAN THE TOP OF THE THRESHOLD.
  9. NO GUTTERS, DOWN SPOUTS OR SPLASH BLOCKS.

2ND FLOOR PLAN  
SCALE: 1/4" = 1'-0"  
AREA: 259 SQ. FT.

AMERICAN  
INGENUITY, INC.

8777 HOLIDAY SPRINGS RD  
ROCKLEDGE, FL 32955-5805  
PH. 321-639-8777 USA

DOMES PLANS FOR:

**DEBYSINGH RESIDENCE**

SHEET TITLE:

2ND FLOOR PLAN

DRAWN BY: N.K.H.  
CHECKED BY: G.B.

DATE: 7.23.15

DRAWING NO: 40\_DEBYSINGH  
REVISION:

SHEET NO.

A-5

COPYRIGHT 2015  
AMERICAN INGENUITY, INC.