


AMERICAN INGENUITY

▲ 34' DOME FLOOR PLANNER ▲

FIRST FLOOR MAX: 851 sq.ft.
 SECOND FLOOR MAX: * 427 sq.ft.
 (TO 5' HEADROOM)
 TOTAL MAX: 1278 sq.ft.

* NO HIGH VAULTED CEILING.
 STAIRS WITH TWO STEP PLATFORM.
 FIVE SECOND FLOOR DORMERS.
 EACH DORMER ADDING 9 SQ.FT



FIRST FLOOR PLAN


ENTRYWAYS MAY CONTAIN BOTH DOORS AND WINDOWS.



EACH OPENING INDICATES A POSSIBLE LOCATION FOR A 2ND FLOOR WINDOW OR DOOR DORMER W/ A 2'x6' CUSTOM DOOR.

TO MEET CODE REQUIRED FIRE EGRESS SIZE BEDROOM WINDOW, INSTALL DOOR DORMER ON 2ND FLOOR ABOVE FIRST FLOOR STANDARD ENTRYWAY, INSTEAD OF INSTALLING A DOOR, INSTALL FIRE EGRESS WINDOW.

FIRE EGRESS ROUGH OPENING IS 29"x42" OR 42"x29". ORDER CASEMENT WINDOW WITH EGRESS HARDWARE.



SECOND FLOOR PLAN

THE CENTER PENTAGON INDICATES THE OUTLINE FOR A CUPOLA. THERE IS INSUFFICIENT HEADROOM FOR A THIRD FLOOR LOFT.

2ND FLOOR DOOR DORMERS CAN ONLY BE LOCATED OVER A 7'-6" ENTRYWAY TO CREATE A BALCONY. OR INSTALL WINDOW INSTEAD OF DOOR FOR FIRE EGRESS.

A SECOND FLOOR DORMER CAN ONLY BE INSTALLED WHEN THERE IS A FIRST FLOOR STANDARD ENTRYWAY DIRECTLY BELOW IT.